

# IPMECD-0152-M3040

## Barrier Rod



### Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

### Technical Specification

#### Basic

Color	Mixed with red and white
Matched Product	DHI-IPMECD-105X series

#### General

Operating Temperature	-35 °C to +65 °C (-31 °F to +149 °F)
Storage Temperature	-35 °C to +65 °C (-31 °F to +149 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90%, non-condensing
Casing Material	Metal (Aluminum)
Product Dimensions	3,000.0 mm × 100.0 mm × 45.0 mm (118.11" × 3.94" × 1.77") (L × W × H)
Net Weight	3.9 kg (8.60 lb)
Gross Weight	5.4 kg (11.90 lb)
Installation	It can be Installed on the boom gate.

### Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-0152-M3040	Barrier Rod

- 3 to 4 m telescopic arm that can be used on either side of the boom gate.
- Made of aluminum alloy, and designed with an anti-rust case that was treated with electrostatic spray.
- Elastic anti-smashing rubber strip at the bottom.

### Dimensions (mm[inch])

