

## GV-NET/IO Card V3.2



The GV-NET/IO card provides 4 inputs and 4 relay outputs. It supports both DC and AC output voltages and provides a USB port as well.

Specifications			
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008	
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 / Server 2012 / Server 2012 R2	
Input	Input	4	
	Input Signal	Dry-Contact Wet-Contact : 9~30V AC/DC	
Output	Relay Output	4	
	Relay Status	Normal Open	
	Relay Capacitance	USB Connection	30V DC, 3A
		RS-232 Connection	125 / 250V AC, 3A 30V DC, 3A
Interface		RJ-11 to DB9	
		RJ-11 to USB	
		3-pin internal USB to internal USB	
Mode Switch	I/O Box Mode	Without GV-Video Capture Card	
	NET/IO Card Mode	With GV-Video Capture Card	
Address		1-4	
Communication		RS-485, USB, RS-232	
Environmental Conditions		0~50°C / 32~122°F , 5%~95% (non-condensing)	
Dimensions (W x H)		90 x 99 ( mm ) / 3.90 x 3.54 (in)	
Installation Guide		<a href="#">GV-NET/IO Card V3.2</a>	

**Note:** All specifications are subject to change without notice.