



REL-DG V2 ORION

OUTPUT RELAYS FOR ORION FIRE AND EXTINGUISHING PANEL

This module allows additional relays for ORION / ORION EX V2, each additional relay is assigned to a specific function. Check manual for functional details.

Each relay circuit got a Red LED to indicate alarm and fault condition, check manual for details.

There is an 8 dip switch to set a delay to a specific relay output, please consult manual for further details.

TECHNICAL SPECIFICATIONS

SUPPLY	20 to 30V DC
QUIESCENT CONSUMPTION	5 mA
ALARM CONSUMPTION	5 mA (Iq) + 7,5 mA per active relay
MAX DRAIN CURRENT PER CIRCUIT	30V DC - 2A / 230V AC - 0.25A
OPER. TEMPERATURE	-10°C to 50°C
MAX HUMIDITY	95% RH non-condensing
COLOUR / MATERIAL	White / ABS
DIMENSIONS	150 (W) x 90 (L) x 32 (H) mm
WEIGHT	216g inc. packaging
COMPATIBILITY	ORION and ORION EX V2

ORDER CODE

REL-DG-4 V2 ORION	EXPANSION MODULE WITH 4 RELAY CIRCUIT
REL-DG- 8 V2 ORION	EXPANSION MODULE WITH 8 RELAY CIRCUIT